

# HM-A300E

## Mobile Label Printer



### Features

- Support iOS/Android
- Support type-C USB charging
- Dual-mode Bluetooth connection
- Large-size LCD display screen
- Support power-saving mode
- The design of large paper compartment is able to contain larger paper roll, which is user-friendly and highly efficient without frequent replacement
- Paper width can be freely adjusted by the sliding-type paper guide, which is compatible with various consumables



Drop Proof



Light



Bluetooth





Type-C USB Charging

## Specification

Items	Specifications	
Printing Spec	Print Method	Direct thermal
	Resolution	203 dpi
	Print Speed	Max.60mm/s
	Print Width	Max.72mm
	Print Protocol	CPCL
Media Spec	Type	Thermal label paper , receipt paper
	Width	25mm-80mm, adjustable
	Paper Roll Outer Diameter	Max.50mm
	Thickness	53μm~150μm
	Paper Outlet Direction	Upward
Communication Interface	Standard	USB Type C, Dual-mode Bluetooth 5.2
Sensor	Standard	Out-of-paper sensor, gap sensor, cover-opening sensor, TPH over temperature sensor, battery temperature sensor
	Optional	Black mark sensor
Hardware	RAM	4MB
	Flash	8MB
	Buzzer	Built-in
	Display	Dots: 96×39
Character and Barcode	Character Spec	Alphanumeric, simplified Chinese, traditional Chinese, English, Multiple international languages
	Barcode	1D Code: Code 39, Code 93, UCC/EAN128, Code 128, Codebar, Interleaved 2-of-5, UPC-A, UPC-E, 2 and 5 digit add-on, EAN-8, EAN-13, 2 and 5 digit add-on, Industrial 2 of5 2D Code: PDF417, QR Code
Cutting Method		Tear bar
Power Supply	Input	AC 100-240V, 50/60Hz
	Output	DC 5V, 1A
Battery Spec	Type	Rechargeable Lithium battery
	Voltage	7.4V
	Capacity	2000mAh
Reliability	TPH Life	50km
	Drop height	1.5m
Environmental Parameters	Operating	0°C~45°C , 25%~85%RH, non-condensing
	Storage	-20°C~70°C, 5%~95%RH, non-condensing
Physical Parameters	Dimensions (L x H x W)	110×117.8×58mm
	Weight	400g (with battery)

## Application



**HPRT**  
Your Future, Printed

**Xiamen Hanin Electronic Technology Co.,Ltd.**

Address: 1-5F, NO.8,Gaoqi South 12th Road,Xiamen,China

Telephone: +86-(0)592-5885993 (English)

E-mail: overseas@hpert.com

Website: www.hpert.com

Brochure Version: 202105



HPRT Official Website