

Accelerate your work efficiency with automatic document feeder.

The new M6550 series with ADF gives home and small business user easier and faster copying and scanning experiences.







3 in 1+ADF



One-step driver installation and direct printing



Office document direct print from mobile devices



Processor Speed/ Memory



Fast Print and Copy Speeds



Wi-Fi Connectivity and Mobile Printing



20000 Page Maximum Monthly Duty Cycle



KEY SPECIFICATIONS



M6550 Series

Monochrome Laser Multifunction Printer

RINTING				
Print speed	22ppm (A4 / 23ppm(Letter)			
Resolution (print, copy & scan)(1)	1200x1200 dpi			
First print out time	Less than 7.8s			
Processor	600 MHZ			
Memory	128MB			
Duplex mode	Manual			
Connectivity	High-Speed USB 2.0	High-Speed USB 2.0 Net: IEEE 802.3 10/100 Base-TX	High-Speed USB 2.0 WiFi: IEEE 802.11b/g/n	High-Speed USB 2.0 Net: IEEE 802.3 10/100Base-TX WiFi: IEEE 802.11b/g/r
Maximum Monthly Duty Cycle	20, 000 pages			
Printer language	GDI			
OPYING				
Copy speed	22ppm (A4 / 23ppm(Letter)			
First copy out time	Less than 10s;ADF: Less than 12s			
Zoom	25% - 400%			
Max. copy pages	1 - 99 pages			
Additional function	ID copy, Receipt copy, N-up copy, Clone copy			
ANNING				
Scanner type	Flatbed+ADF			
Max. scan size	216 x 297mm(Flatbed),216 x 356mm(ADF)			
Color scanning			Yes	
Output function	Scan to PC	Scan to E-mail, PC, FTP		ail, PC, FTP ndroid
PER HANDLING				
Paper input capacity	150 pages			
Paper output capacity	100 pages			
ADF Capacity	35 pages			
Media types	Plain, Thick, Transparency, Cardstock, Label, Envelope and Thin			
Media sizes	A4,A5,A6,JIS B5,ISO B5,B6, Letter, Legal, Executive, Statement, Monarch envelope, DL envelope, C5 envelope, C6 envelope, NO.10 envelope, Japanese Postcard, Folio, O-cio, Big 16k, 32k,16k, Big 32k,ZL, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2			
Media weight	60~163g/m²			
THER				
Operating system compatibility	Server2003/Se Vista/Win7 Mac	Microsoft Windows Server2003/Server2002/XP/ Vista/Win7/Win8/Win8.1/Win10; Mac OS 10.7~10.13; Linux(ubuntu 12.04&14.04) iOS 7.0 and above; Android 4.4 and above		
Dimensions (WxDxH)	417x305x244mm(16.4"×12.0"×11.8")			
Weight (with toner cartridge)	8.5Kg (18.7lb)			
Power	110V Model: AC100~127V(±10%); 50Hz/60Hz; 6A 220V Model: AC220~240V(-15%,+10%); 50Hz/60Hz; 3A			
Recommended temperature	10-32°C (50°F-90°F)"			
Humidity range	20 - 80%			

Toner cartridge⁽²⁾

700 pages starter cartridge; P*-210 series (Standard capacity toner: 1,600 pages)

WWW.PANTLIM.COM EN-WW-20190826

⁽¹⁾ Up to
(2) As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)
Copyright © 2019 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.
*Printer data based on Pantum internal testing.