



## Lexmark MX532adwe

Exceptional performance, secure and sustainable



# Lexmark MX532adwe

With exceptional performance and secure design MX532adwe multi-function printer (copy/scan/print/fax) delivers enhanced productivity, up to 44 ppm\* on A4 paper and a toner yield up to 28,400 pages\*\*. Fast time to first print, superior print quality and easy-to-use touch screen.

## Secure by design

Lexmark expertise helps customers protect their data, their device and their network. Our security ecosystem is designed to overcome the most complex data challenges. And now we've added the Trusted Platform Module (TPM)\*\*\*, which includes on-board authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint. TPM meets stringent industry and US government security standards including Common Criteria and Federal Information Processing Standard (FIPS).

## Proprietary technology

We own core technology across hardware, firmware, services, and solutions, creating seamless connections designed to reduce the risk of security gaps between your document, your device and your network. Our expertise is our customer's benefit.

## Sustainability

With certifications in Energy Star®, Blue Angel, RoHS, EPEAT® Silver. Models are sustainable for today and beyond. Lexmark is an industry leader of recycled content with products using at least 39% PCR content and continual focus on improvement. This line is also engineered for Long Life and designed to last and reduce waste.

## Intelligent Design

Every touch point is designed to withstand high usage while meeting accessibility standards. Steel frames support the device and provide durability to help ensure consistent long-

term performance. Products are designed for long service life with long-life components and are easily serviced with few tools.



## Optimised productivity

Increase productivity with optimised performance. Print at up to 44 pages per minute\* (A4) and capture information quickly with scan speeds of up to 49 images per minute (A4) for one-sided scanning, and up to 98 images per minute (A4) for two-sided scanning.

## Manageability

These IoT-ready devices can be remotely managed, including setup, configuration, consumables management, and diagnostics. Wireless capability gives freedom of access and remote firmware updates make it easy to upgrade to the latest apps and security features. Our mobile printing app makes it easier to monitor and manage your print jobs from remote locations, all from the touch of your phone.


This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

\* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\* Average continuous mono declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19752. Actual yield will vary considerably based upon many factors. See [www.lexmark.com/yields](http://www.lexmark.com/yields) for more information. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Programme (LCCP).

\*\*\* The Trusted Platform Module (TPM) is not available in some countries.

# Lexmark MX532adwe



- 1

**Multifunction product with 10.9 cm touch screen**  
513.7 x 479 x 450 mm
- 2

**250-Sheet output bin**  
Dimensions included as part of base model
- 3

**100-Sheet multipurpose feeder**  
Dimensions included as part of base model
- 4

**550-Sheet tray**  
Dimensions included as part of base model
- 5

**250-Sheet Tray**  
78.1 x 389 x 373.7 mm
- 6

**550-Sheet Tray**  
108.2 x 389 x 373.7 mm

- 7

**550-Sheet Lockable Tray**  
108.2 x 389 x 373.7 mm
- 8

**Adjustable Stand**  
584 x 597 x 597 mm
- 9

**Swivel Cabinet**  
263 x 476 x 600 mm
- 10

**Convenience Stapler HV**  
82 x 109 x 121 mm

Standard

Optional

|            |                                                                                      |
|------------|--------------------------------------------------------------------------------------|
| <b>P/N</b> | <b>Hardware</b>                                                                      |
| 38S0830    | Lexmark MX532adwe                                                                    |
| <b>P/N</b> | <b>Supplies</b>                                                                      |
| 35S8500    | Staple Cartridges                                                                    |
| 66S0HA0    | Lexmark MS531, MX532 28.4K Toner Cartridge                                           |
| 66S0Z00    | Lexmark MS531, 631, 632, 639, MX532, 632, M/XM3350 Return Programme 75K Imaging Unit |
| 66S0ZA0    | Lexmark MS531, 631, 632, 639, MX532, 632 75K Imaging Unit                            |
| 66S2000    | Lexmark MS531, 631, 632, MX532, 632 Return Programme 5K Toner Cartridge              |
| 66S2H00    | Lexmark MS531, MX532 Return Programme 28.4K Toner Cartridge                          |
| <b>P/N</b> | <b>Paper Handling</b>                                                                |
| 38S2910    | 250-Sheet Tray                                                                       |
| 38S3110    | 550-Sheet Tray                                                                       |
| 38S3130    | 550-Sheet Lockable Tray                                                              |
| 47C4590    | Convenience Stapler                                                                  |
| <b>P/N</b> | <b>Memory Options</b>                                                                |
| 27X0400    | 500+ GB Hard Disk                                                                    |
| 57X9528    | Intelligent Storage Drive (ISD)                                                      |
| <b>P/N</b> | <b>Application Solutions</b>                                                         |
| 57X0225    | Desktop Contactless Reader                                                           |
| 57X0235    | Contactless Front Solutions Module (Primary Choice)                                  |
| 57X0300    | Contact Authentication Device                                                        |
| 57X0301    | Contactless Authentication Device                                                    |
| 82S1203    | IPDS License                                                                         |
| 82S1204    | Bar Code License                                                                     |
| <b>P/N</b> | <b>Connectivity</b>                                                                  |
| 1021231    | Parallel (10') Cable                                                                 |
| 1021294    | USB (2 Meter) Cable                                                                  |
| 27X0900    | RS-232C Serial Interface Card                                                        |
| 27X0901    | Parallel 1284-B Interface Card                                                       |
| 27X0912    | Lexmark MarkNet™ N8230 Fiber Ethernet Print Server                                   |
| 57X7040    | English Keyboard Kit                                                                 |
| SPD0002    | Surge Protective Device, 220-240V                                                    |
| <b>P/N</b> | <b>Furniture</b>                                                                     |
| 3073173    | Swivel Cabinet                                                                       |
| 35S8502    | Adjustable Stand                                                                     |

| Product Specifications                        |                                                                                                                                                                       | Lexmark MX532adwe |
|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| Printing                                      |                                                                                                                                                                       |                   |
| Display                                       | Lexmark e-Task 10.9 cm (4.3-inch) colour touch screen                                                                                                                 |                   |
| Print Speed                                   | Up to: Black: 44 ppm <sup>1</sup> (A4)                                                                                                                                |                   |
| Time to First Page                            | As fast as: Black: 6 seconds                                                                                                                                          |                   |
| Print Resolution                              | Black: 1200 x 1200 dpi, 1200 IQ (1200 x 600 dpi)                                                                                                                      |                   |
| Memory                                        | Standard: 2048 MB / Maximum: 2048 MB                                                                                                                                  |                   |
| Hard Disk                                     | Intelligent Storage Drive available; Magnetic Hard Disk available                                                                                                     |                   |
| Recommended Monthly Page Volume               | 2,000 - 15,000 pages <sup>2</sup>                                                                                                                                     |                   |
| Maximum Monthly Duty Cycle                    | Up to: 120,000 pages per month <sup>3</sup>                                                                                                                           |                   |
| Copying                                       |                                                                                                                                                                       |                   |
| Copy Speed                                    | Up to: Black: 44 cpm <sup>1</sup> (A4)                                                                                                                                |                   |
| Time to First Copy                            | as fast as: Black: 6.5 seconds                                                                                                                                        |                   |
| Scanning                                      |                                                                                                                                                                       |                   |
| ADF Scan                                      | DADF (single pass Duplex)                                                                                                                                             |                   |
| A4/Ltr Duplex Scan Speed                      | Up to: Black: 98/104 sides per minute / Colour: 68/72 sides per minute                                                                                                |                   |
| A4/Ltr Simplex Scan Speed                     | Up to: Black: 49/52 sides per minute / Colour: 34/36 sides per minute                                                                                                 |                   |
| ADF Paper Input Capacity                      | Up to: 100 pages 75 gsm bond                                                                                                                                          |                   |
| Faxing                                        |                                                                                                                                                                       |                   |
| Modem Speed                                   | ITU T.30, V.34 Half-Duplex, 33.6 Kbps                                                                                                                                 |                   |
| Supplies <sup>4</sup>                         |                                                                                                                                                                       |                   |
| Laser Cartridge Yields                        | up to: 28,400 <sup>5</sup> -page Black Cartridge                                                                                                                      |                   |
| Imaging Unit Estimated Yield                  | Up to: 75,000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage                                                                          |                   |
| Cartridge(s) Shipping with Product            | 5,000 <sup>5</sup> -page Return Program Toner Cartridge <sup>5</sup>                                                                                                  |                   |
| Paper Handling                                |                                                                                                                                                                       |                   |
| Included Paper Handling                       | 100-Sheet Multipurpose Feeder, 250-Sheet Output Bin, Integrated Duplex, 550-Sheet Input                                                                               |                   |
| Optional Paper Handling                       | 550-Sheet Lockable Tray, 250-Sheet Tray, 550-Sheet Tray                                                                                                               |                   |
| Paper Input Capacity                          | Up to: Standard: 650 pages 75 gsm bond / Maximum: 2300 pages 75 gsm bond                                                                                              |                   |
| Paper Output Capacity                         | Up to: Standard: 250 pages 75 gsm bond / Maximum: 250 pages 75 gsm bond                                                                                               |                   |
| Media Types Supported                         | Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide                                                                          |                   |
| Media Sizes Supported                         | A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki Card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope   |                   |
| General Information <sup>6</sup>              |                                                                                                                                                                       |                   |
| Standard Connectivity                         | Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), USB 2.0 Specification Hi-Speed Certified (Type B), 802.11b/g/n/ac + BLE |                   |
| Optional Network Ports / Optional Local Ports | MarkNet N8230 Fiber Ethernet Print Server / Internal 1284-B Bidirectional Parallel, Internal RS-232C serial                                                           |                   |
| Noise Level                                   | Operating: 55 dBA (Print) / 57 dBA (Copy) / 52 dBA (Scan)                                                                                                             |                   |
| Specified Operating Environment               | Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 Metres (9,500 Feet) / Humidity: 15 to 80% Relative Humidity                                                 |                   |
| Product Guarantee                             | 1-Year Onsite Service, Next Business Day                                                                                                                              |                   |
| Size / Weight                                 | H x W x D: 513.7 x 479 x 450 mm / 21.2 kg                                                                                                                             |                   |
| ENERGY STAR Typical Electricity Consumption   | TEC: 0.58 kilowatt-hours per week                                                                                                                                     |                   |

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

<sup>1</sup> Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

<sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details. <sup>5</sup> Average standard page yield value declared in accordance with ISO/IEC 19752. <sup>6</sup> Printers are sold subject to certain license/agreement conditions. See [www.lexmark.com/printerlicense](http://www.lexmark.com/printerlicense) for details.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2023 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).

