

TECHNICAL SPECIFICATIONS

PIXMA TS3355

GENERAL SPECIFICATIONS

Functions

Wi-Fi, Print, Copy, Scan, Cloud

PRINTER SPECIFICATIONS

Print Resolution

Up to 4800^[1] x 1200 dpi

Print Technology

2 FINE Cartridges (Black and Colour)

Mono Print Speed

Approx. 7.7 ipm^[2]

Colour Print Speed

Approx. 4.0 ipm^[2]

Photo Print Speed

Borderless 10x15cm : Approx. 65 seconds^[2]

Borderless Printing

Yes (13x18cm, 10x15cm, 13x13cm)

Two Sided Printing

Manual operation

CARTRIDGES AND YIELDS

Standard Ink Cartridges

PG-545 (Black)

CL-546 (Colour)

Optional XL Ink Cartridges

PG-545XL (Black)

CL-546XL (Colour)

Cartridge Yield (Plain paper)

A4 colour documents printing^[3]

Black: 180 pages

Black XL: 400 pages

Colour: 180 pages

Colour XL: 300 pages

Paper Types

Plain Paper

Envelopes

Photo Paper Plus Glossy II (PP-201)

Photo Paper Glossy "Everyday Use" (GP-501)

Removable Photo Stickers (RP-101)

Magnetic Photo Paper (MG-101)

Maximum Paper Input

Rear tray: Max. 60 sheets (plain paper)

Paper Sizes

Plain paper: A4, A5, B5, Letter, Legal

Photo paper: 13x18cm, 10x15cm, 13x13cm

[Custom size]

width 101.6 mm - 215.9 mm, length 127 mm - 676 mm

Plain paper: 64 - 105 g/m²

Canon photo paper: up to 275 g/m²

Paper Weight

SCANNER SPECIFICATIONS

Scanner Type

CIS flatbed photo and document scanner

Scanner Resolution (Optical)

600 x 1200 dpi^[4]

Scanning Depth (Input / Output)

Colour: RGB each 16bit/8bit

Greyscale: 16 bit / 8 bit

Maximum Document Size

216 x 297 mm

COPIER SPECIFICATIONS

Copy Speed

sFCOT: Approx. 27 sec^[5]

sESAT: Approx. 3 ipm^[5]

Multiple Copy

20 copies (max.)

Copy Functions

Document copying, Borderless copy

Copy Zoom

Fit to page^[6]

Document Size

216 x 297 mm

INTERFACE

Display Type & Size

3.8cm LCD segment mono

Interface Type - PC / Mac

Hi-Speed USB (B Port)

Wi-Fi: IEEE802.11 b/g/n

Wi-Fi Security: WPA-PSK, WPA2-PSK, WEP, Administration password

Wireless LAN Frequency Band: 2.4GHz

Interface Type - Other

Canon PRINT Inkjet/SELPHY app

Easy-PhotoPrint Editor

Message In Print app

PIXMA Cloud Link

Canon Print Service Plugin (Android)

Google Cloud Print

Apple AirPrint

Access Point Mode

WLAN PictBridge

Mopria (Android)

SOFTWARE

Supported Operating Systems

Windows 10, Windows 8.1, Windows 7 SP1
Operation can only be guaranteed on a PC with pre-installed Windows 7 or later.

OS X 10.11.6, macOS 10.12~macOS 10.14

iOS, Android, Windows 10 Mobile

Windows: 2.0GB or more

Mac: 1.0GB or more

Note: for bundled software installation. The necessary amount of hard disk space required.

Display: 1024 x 768 XGA

MP Driver including Scanning Utility

Easy-PhotoPrint Editor (download)

Supported Mobile Systems

Minimum System Requirements

Software Included

PHYSICAL FEATURES

Weight

approx. 3.9 kg

Dimensions (W x D x H)

approx. 435 x 316 x 145 mm

Acoustic Noise Levels

approx. 53.5dB(A)^[6]

Recommended Operating Environment

Temperature: 15-30°C

Humidity: 10-80%RH (no dew condensation)

Power Source

AC 100-240V, 50/60Hz

Power Consumption

Off: Approx. 0.3W

Standby (connected to PC via USB): Approx. 1.7W (scanning lamp off)

Standby (all ports connected): Approx. 1.7W (scanning lamp is off)

Time to enter Standby mode: 10min 38sec

Copying: Approx. 11W^[7]

Footnotes

[1] Ink droplets can be placed with a minimum pitch of 1/4800 inch

[2] Document print speeds are the averages of ESAT in Office Category Test for the default simplex mode, ISO/IEC 24734.

[3] Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer.

[4] Declared yield value in accordance with ISO/IEC 24711 standard. Values obtained by continuous printing.

[5] Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.

[6] Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183.

[7] Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.

[8] Acoustic Noise is measured based on ISO7779 standard (colour printing) with default setting.

[9] When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.

[10] Only available for L/4x6/2L/5x7/5x5 Square

Standard disclaimers

All specifications subject to change without notice.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield

Scan speed may vary depending on system configuration, interface, software, scan mode settings and document size etc.

Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.

All brand and product names are trademarks of their respective companies.

Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

Live for the story_

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
Canon Europa NV 2019