

## NTW Weighing Indicator

### General Specifications

- Display 52mm digit LCD display, with white LED backlight
- Keyboard 7 keys (Mechanical switch)
- Housing ABS plastic
- Max. Divisions 6,000e; 30,000d
- Load cell excitation voltage 5V/150mA
- ADC update  $\leq 1/10$  second
- Operating Temp.  $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
- Power AC adapter (12V/500mA), rechargeable battery (6V/4Ah)
- Gross weight 3kg
- Packing Master carton holds 4, dimension 0.07 m<sup>3</sup>



- Easy to use, front panel configuration
- Applications: 1. Accumulation 2. Check weighing 3. Net/gross shift  
4. Weighing unit conversion 5. Peak hold 6. Animal weighing
- OIML approval from DELTA (approval no.DK0199.165)
- Keyboard lock function
- Optional RS-232 interface
- Optional analog output (0-10V/4-20mA)
- Optional setpoint output (HI/OK/LOW/BEEP)
- Optional blue tooth



## NTW Weighing Indicator

| Model Name | Capacity | Readability | Division | Approx. weight | Approval |
|------------|----------|-------------|----------|----------------|----------|
| NTW        | X        | X           | 30,000d  | 3kg            | CE       |

### Options



### Dimensions(mm)

