

TECHNICAL SPECIFICATIONS

PIXMA TR4550

GENERAL SPECIFICATIONS

Functions Wireless, Print, Copy, Scan, Fax & Cloud Link

PRINTER SPECIFICATIONS

Print Resolution Up to 4800^[1] x 1200 dpi
Print Technology 2 FINE Cartridges (BK, CL)
Mono Document Print Speed Approx. 8.8 ipm^[2]
Colour Document Print Speed Approx. 4.4 ipm^[2]
Photo Print Speed Borderless 10x15cm: Approx. 65 seconds^[3]
Borderless Printing Yes (A4, LTR, 20x25cm, 13x18cm, 10x15cm)
Two Sided Printing Auto Duplex Print (A4, LTR - plain paper)

SCANNER SPECIFICATIONS

Scanner Type Flatbed & ADF
Scanner Resolution (Optical) Up to 600 x 1200 dpi^[4]
Maximum Document Size Flatbed: A4, LTR (216x297mm)
ADF: A4, LTR, LGL
Scanning Depth (Input / Output) Colour: RGB each 16bit/8bit
Greyscale: 16 bit / 8 bit

COPIER SPECIFICATIONS

Copy Speed - Colour Document sFCOT: Approx. 27 seconds^[6]
sESAT: Approx. 3.6 ipm^[6]
sESAT ADF: Approx. 2.7 ipm^[6]
Multiple Copy max. 99 pages
Copy zoom 25-400%
Fit to page
Copy functions Document Copying, Borderless copy, 2-sided copy,
2-on-1 and 4-on-1 copy, Frame erase copy,
Collated copy (ADF only) ID copy
Copy quality settings 3 positions (Draft, Standard, High)

FAX SPECIFICATIONS

Fax Type Super G3/Color Communication
Fax Resolution 8pels/mm x 3.85lines/mm(Standard)
8pels/mm x 7.7lines/mm(Fine)
300dpi x 300dpi (Extra Fine)
Fax Speed Mono: approx. 3 sec. (33.6kbps)^[7]
Colour: approx. 1 min. (33.6kbps)^[7]
Fax Memory approx. 50 pages

COMPATIBLE INKS

Standard Ink Cartridges PG-545 (Black)
CL-546 (Colour)
Optional XL Ink Cartridges PG-545XL (Black)
CL-546XL (Colour)

INK YIELDS

BK (Pigment Black) Black: 180 pages
Black XL: 400 pages
CL (Colour - CMY) Colour: 180 pages
Colour XL: 300 pages
Testing standards ISO/IEC 24711 for A4 colour document pages
Values obtained by continuous printing
* Estimated supplemental yield

PAPER SUPPORT

Paper Types Plain Paper
Photo Paper Pro Platinum (PT-101)
Photo Paper Plus Glossy II (PP-201)
Photo Paper Pro Luster (LU-101)
Photo Paper Plus Semi-gloss (SG-201)
Glossy Photo Paper "Everyday Use" (GP-501)
Matte Photo Paper (MP-101)
Removable Photo Stickers(RP-101)
Magnetic Photo Paper(MG-101)
Maximum Paper Input Max. 100 sheets of plain paper
Max. 20 sheets of photo paper
Paper Sizes A4, A5, B5, LTR, LGL, 13x18cm, 10x15cm
Envelopes(DL,COM10)
[Custom size](width 89 mm - 215.9 mm, length 127 mm - 676 mm)
Paper Weight Plain paper: 64 - 105 g/m²
Canon photo paper up to 300 g/m² (PT-101)

INTERFACE

Interface Type - PC / Mac Hi-Speed USB (B Port)
Wi-Fi: IEEE802.11 b/g/n
Wi-Fi Security: WPA-PSK, WPA2-PSK, WEP,
Administration password
Wireless LAN Frequency Band: 2.4GHz
Interface Type - OTHER PIXMA Cloud Link (from smartphone / tablet)
Canon PRINT Inkjet/SELPHY app
Canon Print Service Plugin (Android)
Google Cloud Print
Apple AirPrint
Mopria (Android)
Message In Print app
Wireless Direct
Access point mode

SOFTWARE

Supported Operating System Windows 10, Windows 8.1, Windows 7 SP1
Operation can only be guaranteed on a PC with pre-installed Windows 7 or later.
.NET Framework 4.5.2 or 4.6 is required
OS X 10.10.5~OS X 10.11, macOS 10.12~macOS 10.13
Supported Mobile Systems iOS
Android
Windows 10 Mobile
Minimum System Requirements Windows: 3.1 GB disk space, Internet Explorer 8
Mac: Internet connection, 1.5GB disk space, Safari 5
Display: 1024 x 768 XGA
Software Included MP Driver including Scanning Utility
Easy-WebPrint EX (download)^[10]

Live for the story_

TECHNICAL SPECIFICATIONS

PIXMA TR4550

PHYSICAL FEATURES

Display Type & Size Display languages

Full dot LCD display
33 Languages Selectable: Japanese/English(mm & inch)/German/French/Italian/Spanish/Dutch/Portuguese/Norwegian/Swedish/Danish/Finnish/Russian/Czech/Hungarian/Polish/Slovene/Turkish/Greek/Simplified Chinese/Traditional Chinese/Korean/Indonesian/Slovakian/Estonian/Latvian/Lithuanian/Ukrainian/Romanian/Bulgarian/Croatian/Vietnamese

Automatic Document Feeder

Dimensions (W x D x H)

Up to 20 Sheets (1-sided)
approx. 435 x 295 x 189 mm

Weight

5.9 kg

Power Source

AC 100-240V, 50/60Hz

Power Consumption

Off: Approx. 0.2W
Standby (USB connection to PC): Approx. 0.9W (scanning lamp off)
Standby (all ports connected): Approx. 1.6W (scanning lamp off)
Time to enter Standby mode: 10min 46sec
Copying: Approx. 8W^[8]
Approx. 54dB(A)^[9]

Acoustic Noise Levels (Photo 4x6)

Operating Temperature

15-30°C

Operating Humidity

10-90%RH (no dew condensation)

Footnotes

- ^[1] Ink droplets can be placed with a minimum pitch of 1/4800 inch
- ^[2] Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- ^[3] Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- ^[4] Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.
- ^[5] TBD
- ^[6] Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.
- ^[7] Black & white document fax transmission speed is based on default setting using ITU-T No.1 chart. Color document fax transmission speed is based on default setting using Canon Color Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.
- ^[8] Copy:When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
- ^[9] Acoustic Noise is measured based on ISO7779 standard with default setting.
- ^[10] Easy-WebPrint EX requires Internet Explorer 8 or later

Standard disclaimers

- All specifications subject to change without notice.
- Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- Scan speed may vary depending on system configuration, interface, software, scan mode settings and document size etc.
- Copy speed may vary depending on document complexity, copy mode, page coverage; type of paper used etc. and does not take into account warming up time.
- Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For more information see www.canon-europe.com/ink/yield
- All brand and product names are trademarks of their respective companies.

