

Godex is proud to present the newest addition to our line of printers. C690LJ is a color inkjet label printer for professional use. The printer has the latest sensor technology, high-precision print and easy label handling. This robust all-metal case makes it ideal for industrial use. This unique printer provides professional quality label printing and high printing speed. C690LJ is the ultimate solution for great color label.

The printer has an externally mounted roll holder and a manual tear-off edge. The roller holder allows the use of label rolls with a diameter of up to 228.6cm. Other options such as an automatic rewinder are available.

Label possibilities:









Highlights:

- Full color labels. Waterproof and alcohol resistant
- Large print surface (38x12mm to 210x500mm) up to A4 in size
- High level print quality up to 1200 x 1200dpi in color
- Print speeds up to 4" per second (300dpi)
- Separate large ink cartridges (C/M/Y/B)
- Easy-to-use operation for users









| Print Method | Thermal Inkjet | | | | |
|-----------------------------------|--|-------------------------|------------------|--------------|---------------|
| Tim Memod | Black: up to 1200dpi | | | | |
| Resolution | Color: up to 1200dpi | | | | |
| Print Speed | Up to 4" per second (300dpi) | | | | |
| Ink Volume | Black: 69ml (dye ink), | 66ml (pigment ink), C | olor (CMY): 28ml | | |
| Supported operating system | Windows [®] 8.1, 8, 7, V | ista (32 and 64 bit) XP | | | |
| Sensors | Adjustable GAP, Black Mark sensor from 0 to 3.2" | | | | |
| Media Dimension | | Max | Min | _ | Media width |
| | Label width | 203 mm (8") | 38 mm (1.5") | | |
| | Media width | 216 mm (8.5") | 38 mm (1.5") | 1 | Label Width |
| | Label height | 500 mm (19,7") | 15 mm (0.6") | Label Height | |
| | Label distance | 5 mm (0,02") | 2 mm (0.08") | I | |
| Paper feed | Sensor Supervised label feed Single sheets (manual) GAP between | | | | |
| Material type | Continuous paper ar | | | = | |
| Label roll | Max. Roll diameter 228.6 mm (9") Max. Roll width 219 mm (8.5") | | | | |
| Label detection | GAP, Black Mark, Continous | | | | |
| Interface | Integrated Wired Eth | ernet interface RJ45 US | SB 2.0 | - | $\overline{}$ |
| External power supply | 100-240V AC (+/- 10% | %), 50/60 Hz (+/- 3%) | | | |
| Power consumption (Max) | 28W during printing 6W idle 0.6W (220V) in the of 0.4W (110V) in the of | f state | | | |
| Dimensions (W x H x D) and weight | 500 (B) x 400 (H) x 250 | | | | |
| Warranty | 2 year warranty or 1 | | | | |